

Model(s) UltraTec XT 2000 Hunting and Target
Model Year 2002
Limbs XT 2000 (14")
Cable Guard Bar 8.50
Limb Bolt Length 2.5
Pocket 22/23

Date 3/7/2002

Revision E

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	YBC
Command CL/CH 2UT2HT	65 / 75%	6 1/2	37 5/8	21	1	A	50.5	38.5
	65 / 75%	6 1/2	37 5/8	22	1	C	50.5	38.5
	65 / 75%	6 1/2	37 5/8	23	1	E	50.5	38.5
	65 / 75%	6 1/2	37 5/8	24	1	G	50.5	38.5
	65 / 75%	6 1/2	38 1/4	25	2	C	53.5	39.0
	65 / 75%	6 1/2	38 1/4	26	2	F	53.5	39.0
	65 / 75%	6 3/4	38 3/8	27	3	B	57.5	39.0
	65 / 75%	6 3/4	38 3/8	28	3	D	57.5	39.0
	65 / 75%	6 3/4	38 3/8	29	3	F	57.5	39.0
	65 / 75%	6 3/4	38 1/2	30	4	D	60.0	39.0
	65 / 75%	6 3/4	38 1/2	31	4	F	60.0	39.0
	65 / 75%	6 3/4	38 1/2	32	4	H	60.0	39.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	DT Idler	DT String	CBC	IYBC
Excel EC 2UT2HT	60 / 75%	7	37 5/8	25	1	3.0	58.0	44.5	39.5
	60 / 75%	7	37 5/8	25.5	1.5	3.0	58.0	44.5	39.5
	60 / 75%	7	37 5/8	26	2	3.0	58.0	44.5	39.5
	60 / 75%	7	37 5/8	26.5	2.5	3.0	58.0	44.5	39.5
	60 / 75%	7	37 5/8	27	3	3.0	58.0	44.5	39.5
	60 / 75%	7	38	27.5	4	4.0	59.5	45.5	40.0
	60 / 75%	7	38	28	4.5	4.0	59.5	45.5	40.0
	60 / 75%	7	38	28.5	5	4.0	59.5	45.5	40.0
	60 / 75%	7	38	29	5.5	4.0	59.5	45.5	40.0
	60 / 75%	7	38	29.5	6	4.0	59.5	45.5	40.0
	60 / 75%	7	37 5/8	30	6.5	5.0	60.5	45.5	39.5
	60 / 75%	7 3/8	37 5/8	30.5	7	5.0	60.5	45.5	39.5
60 / 75%	7 3/8	37 5/8	31	7.5	5.0	60.5	45.5	39.5	
60 / 75%	7 3/8	37 5/8	31.5	8	5.0	60.5	45.5	39.5	

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	DT Idler	DT String	CBC	IYBC
Versa VC 2UT2HT	60 / 75%	6 3/4	38 1/4	25	1	A-1	3	57.5	44.5	41.0
	60 / 75%	6 3/4	38 1/4	26	1	C-3	3	57.5	44.5	41.0
	60 / 75%	6 3/4	38 1/4	27	1	E-5	3	57.5	44.5	41.0
	60 / 75%	7	38	28	2	D-4	4	59.5	45.0	41.0
	60 / 75%	7	38	29	2	F-6	4	59.5	45.0	41.0
	60 / 75%	7	38 5/8	30	3	D-4	5	63.0	45.5	41.5
	60 / 75%	7	38 5/8	31	3	F-6	5	63.0	45.5	41.5
	60 / 75%	7	38 5/8	32	3	H-8	5	63.0	45.5	41.5

Letoff, brace height, axle to axle length given as a general production guide only