

Model(s) **ProTec**  
 Model Year **2006**  
 Limbs **XT4000**  
 Cable Guard Bar **10**  
 Limb Bolt Length **2 1/2**  
 Pocket **#25 & #26**

Date **12/8/2005**

Revision

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
cam & 1/2 adjustable	65/75	8 1/2	45 3/8	29	E	C&1/2 #1	58.5	49	46.75
	65/75	8 1/2	45 1/2	30	E	C&1/2 #2	59.5	49.25	47
	65/75	8 9/16	45 1/2	31	E	C&1/2 #3	60.5	49.5	47
	65/75	8 5/8	45 9/16	32	E	C&1/2 #4	61.25	49.5	46.75
	65/75	8 5/8	45 9/16	33	E	C&1/2 #5	62.75	49.75	47
	65/75	8 3/4	45 3/4	34	E	C&1/2 #6	64.25	50.25	47.25
	65/75	8 3/4	46	35	E	C&1/2 #7	65.75	51	47.5

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
wheel & 1/2	65%	9	44 3/8	27	0.0	61	49	45.75
	65%	9	44 3/8	27 1/2	0.5	61	49	45.75
	65%	9	44 3/8	28	1.0	61	49	45.75
	65%	9	44 3/8	28 1/2	1.5	61	49	45.75
	65%	9	44 3/8	29	2.0	61	49	45.75
	65%	9	44 3/8	29 1/2	2.5	61	49	45.75
	65%	9	44 3/8	30	3.0	61	49	45.75
	65%	9 3/16	44 3/16	30 1/2	3.5	64.25	49.75	45.75
	65%	9 3/16	44 3/16	31	4.0	64.25	49.75	45.75
	65%	9 3/16	44 3/16	31 1/2	4.5	64.25	49.75	45.75
	65%	9 3/16	44 3/16	32	5.0	64.25	49.75	45.75
	65%	9 3/16	44 3/16	32 1/2	5.5	64.25	49.75	45.75
	65%	9 3/16	44 3/16	33	6.0	64.25	49.75	45.75
	65%	9 1/4	44 3/4	33 1/2	6.5	68.75	51.25	46.5
	65%	9 1/4	44 3/4	34	7.0	68.75	51.25	46.5
	65%	9 1/4	44 3/4	34 1/2	7.5	68.75	51.25	46.5
65%	9 1/4	44 3/4	35	8.0	68.75	51.25	46.5	