

Model(s) Sapphire XT 2000 Target  
 Model Year 2001  
 Limbs XT 2000 (15" Magnum)  
 Cable Guard Bar  
 Limb Bolt Length 2.25  
 Pocket

Date 1/23/2001

Revision

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
	65%	6 1/2	34 3/8	21	1	B	47.0	36.5
AccuWheel	65%	6 1/2	34 3/8	22	1	D	47.0	36.5
A	65%	6 1/2	34 3/8	23	2	B	48.5	36.5
SH5TA	65%	6 1/2	34 3/8	24	2	D	48.5	36.5
	65%	6 1/2	34 3/8	25	2	F	48.5	36.5
	65%	6 7/8	33 3/4	26	3	D	51.5	36.5
	65%	6 7/8	33 3/4	27	3	F	51.5	36.5
	65%	6 7/8	33 3/4	28	3	H	51.5	36.5

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Idler Wheel	String	Buss Cable
	60 / 75%	7 1/8	35	24	1	3	90.5	37.0
Saber				24.5	1.5	3	90.5	37.0
B	60 / 75%	7 1/8	35	25	2	3	90.5	37.0
SH5TB				25.5	2.5	3	90.5	37.0
	60 / 75%	7 1/8	35	26	3	3	90.5	37.0
				26.5	3.5	3	90.5	37.0
	60 / 75%	7 1/8	35 1/8	27	4	4	93.0	37.5
				27.5	4.5	4	93.0	37.5
	62 / 75%	7 1/8	35 1/8	28	5	4	93.0	37.5

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
	65%	6 5/8	33 7/8	21	1	A	46.5	36.0
Command	65%	6 5/8	33 7/8	22	1	C	46.5	36.0
C/D	65%	6 5/8	33 7/8	23	1	E	46.5	36.0
SH5TC/D	75 / 65%	6 5/8	33 7/8	24	2	B	49.5	36.5
	75 / 65%	6 1/2	34 3/8	25	2	D	49.5	36.5
	75 / 65%	6 1/2	34 3/8	26	2	F	49.5	36.5
	75 / 65%	6 3/4	34 3/8	27	3	B	53.0	37.0
	75 / 65%	6 3/4	34 3/8	28	3	D	53.0	37.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Idler Wheel	String	Buss Cable
	60 / 75%	6 1/2	35	24	1	1	88.0	39.0
	60 / 75%	6 1/2	35	24.5	1.5	1	88.0	39.0
	60 / 75%	6 1/2	35	25	2	1	88.0	39.0
Redline	60 / 75%	6 1/2	35	25.5	2.5	1	88.0	39.0
Z	60 / 75%	6 1/2	35	26	3	1	88.0	39.0
SH5TZ	60 / 75%	6 1/2	35	26.5	3.5	1	88.0	39.0
	60 / 75%	6 1/2	35	27	4	1	88.0	39.0
	60 / 75%	6 1/2	35	27.5	4.5	1	88.0	39.0
	60 / 75%	6 3/8	35 1/2	28	5	2	92.5	40.0
	60 / 75%	6 3/8	35 1/2	28.5	5.5	2	92.5	40.0