

Model(s) ProTec XT 2000 Target
 Model Year 2001
 Limbs XT 2000 (15" Magnum)
 Cable Guard Bar
 Limb Bolt Length 2.25
 Pocket

Date 1/17/2001

Revision

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
	65%	8	39 1/8	22	1	A	51.5	41.5
AccuWheel	65%	8	39 1/8	23	1	C	51.5	41.5
A	65%	8	39 1/8	24	1	E	51.5	41.5
PR5TA	65%	7 7/8	38 7/8	25	2	C	53.0	41.5
	65%	7 7/8	38 7/8	26	2	E	53.0	41.5
	65%	7 7/8	38 7/8	27	2	G	53.0	41.5
	65%	7 3/4	39 3/8	28	3	B	57.5	42.0
	65%	7 3/4	39 3/8	29	3	E	57.5	42.0
	65%	7 3/4	39 3/8	30	3	G	57.5	42.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Idler Wheel	String	Buss Cable
	60 / 75%	8 1/4	40 1/8	27	1	3	100.5	42.0
	60 / 75%	8 1/4	40 1/8	27.5	1.5	3	100.5	42.0
	60 / 75%	8 1/4	40 1/8	28	2	3	100.5	42.0
Saber	60 / 75%	8 1/4	40 1/8	28.5	2.5	3	100.5	42.0
B	60 / 75%	8 1/4	40 1/8	29	3	3	100.5	42.0
PR5TB	60 / 75%	8 1/4	40 1/8	29.5	3.5	3	100.5	42.0
	60 / 75%	8 3/8	40 1/2	30	4	4	103.5	42.5
	60 / 75%	8 3/8	40 1/2	30.5	4.5	4	103.5	42.5
	60 / 75%	8 3/8	40 1/2	31	5	4	103.5	42.5
	60 / 75%	8 3/8	40 1/2	31.5	5.5	4	103.5	42.5
	60 / 75%	8 3/8	40 1/2	32	6	4	103.5	42.5
	60 / 75%	8 3/8	40 1/2	32.5	6.5	4	103.5	42.5
	60 / 75%	8 3/8	40 5/8	33	7	5	106.0	43.0
	60 / 75%	8 3/8	40 5/8	33.5	7.5	5	106.0	43.0
	60 / 75%	8 3/8	40 5/8	34	8	5	106.0	43.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
	65%	7 1/2	40 1/4	24	1	B	53.0	42.0
	65%	7 1/2	40 1/4	25	1	D	53.0	42.0
Command	65%	7 1/2	40 1/4	26	1	F	53.0	42.0
C/D	75 / 65%	7 1/2	40 1/8	27	2	B	55.5	42.0
PR5TC/D	75 / 65%	7 1/2	40 1/8	28	2	E	55.5	42.0
	75 / 65%	7 1/2	40 1/8	29	2	G	55.5	42.0
	75 / 65%	7 3/4	39 7/8	30	3	C	58.5	42.5
	75 / 65%	7 3/4	39 7/8	31	3	F	58.5	42.5
	75 / 65%	7 3/8	41	32	4	C	62.0	43.0
	75 / 65%	7 3/8	41	33	4	E	62.0	43.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	Buss Cable
	65%	7 7/8	39 3/8	27	1.5	53	41.5
	65%	7 7/8	39 3/8	27.5	2	53	41.5
	65%	7 7/8	39 5/8	28	2.5	54.5	41.5
Master	65%	7 7/8	39 5/8	28.5	3	54.5	41.5
X	65%	7 3/4	40 1/8	29	3.5	55.5	42.0
PR5TX	65%	7 3/4	40 1/8	29.5	4	55.5	42.0
	65%	7 1/2	40 1/2	30	4.5	57.5	42.5
	65%	7 1/2	40 1/2	30.5	5	57.5	42.5
	65%	7 1/2	40 3/4	31	5.5	59	42.5
	65%	7 1/2	40 3/4	31.5	6	59	42.5
	65%	7 5/8	40 3/4	32	6.5	60.5	42.5
	65%	7 5/8	40 3/4	32.5	7	60.5	42.5
	65%	7 5/8	40 3/4	33	7.5	60.5	42.5
	65%	7 5/8	40 3/4	33.5	8	60.5	42.5

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Idler Wheel	String	Buss Cable
	60 / 75%	8	39 1/2	27	1	1	97.0	43.5
	60 / 75%	8	39 1/2	27.5	1.5	1	97.0	43.5
	60 / 75%	8	39 1/2	28	2	1	97.0	43.5
Redline	60 / 75%	8	39 1/2	28.5	2.5	1	97.0	43.5
Z	60 / 75%	8	39 1/2	29	3	1	97.0	43.5
PR5TZ	60 / 75%	8	39 1/2	29.5	3.5	1	97.0	43.5
	60 / 75%	8	39 1/2	30	4	1	97.0	43.5
	60 / 75%	8	39 1/2	30.5	4.5	1	97.0	43.5
	60 / 75%			31	5	2	101.5	44.5
	60 / 75%			31.5	5.5	2	101.5	44.5
	60 / 75%			32	6	2	101.5	44.5
	60 / 75%			32.5	6.5	2	101.5	44.5
	60 / 75%			33	7	2	101.5	44.5
	60 / 75%	7 5/8	40 5/8	33.5	7.5	2	103.5	45.5
	60 / 75%	7 5/8	40 5/8	34	8	2	103.5	45.5