

Model(s) 38 Pro XL
Model Year 2007
Limbs XT 3000
Cable Guard Bar 10 1/2
Stealth shot bar None
Limb Bolt Length 2 1/2
Pocket 31 & 32

Date

Revision

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
Cam & 1/2 Adjustable	65/75	8 7/8	42 7/16	28	D	1	55.5	46	43.75
	65/75	8 7/8	42 3/16	29	D	2	56.25	46.25	43.75
	65/75	9	42 5/16	30	D	3	57.5	46.75	44
	65/75	8 7/8	42 1/2	31	D	4	59.25	47.5	44.5
	65/75	8 7/8	42 11/16	32	D	5	60.5	47.75	44.75

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable	Cam Size
C2 Cam	65%	8 3/4	41 5/8	27 1/2	0.5	55.5	46.75	43.75	Base Size 1
	65%	8 3/4	41 9/16	28	1	55.5	46.75	43.75	
	65%	8 3/4	41 5/8	28 1/2	1.5	55.5	46.75	43.75	
	65%	8 3/4	41 5/8	29	2	55.5	46.75	43.75	
	65%	8 3/4	41 13/16	29 1/2	2.5	58.25	46.75	44.25	Base Size 2
	65%	8 3/4	41 11/16	30	3	58.25	46.75	44.25	
	65%	8 3/4	41 3/4	30 1/2	3.5	58.25	46.75	44.25	
	65%	8 3/4	42 1/16	31	4	60.75	47.25	44.75	Base Size 3
	65%	8 11/16	42	31 1/2	4.5	60.75	47.25	44.75	
	65%	8 3/4	42 1/16	32	5	60.75	47.25	44.75	
	65%	8 3/4	42 5/16	32 1/2	5.5	63.75	47.75	44.75	Base Size 4
	65%	8 3/4	42 5/16	33	6	63.75	47.75	44.75	
65%	8 13/16	42 3/8	33 1/2	6.5	63.75	47.75	44.75		