

**Model(s)** ProElite  
**Model Year** 2004  
**Limbs** XT3000  
**Cable Guard Bar** 10 1/2  
**Limb Bolt Length** 2 1/2  
**Pocket** 27 & 28 Low

**Date** 12/15/03  
  
**Revision**

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	HCBC	HYBC
	65 / 75%	8 1/4	41 3/4	27	C	A-1	54.5	45.5	43.25
Cam	65 / 75%	8 3/8	41 3/4	28	C	B-2	55.5	45.75	43.5
&1/2	65 / 75%	8 1/2	41 1/2	29	C	C-3	56.5	45.75	43.25
Adjustable	65 / 75%	8 5/8	41 5/8	30	C	D-4	58.0	46.25	43.5
	65 / 75%	8 3/4	41 1/2	31	C	E-5	59.0	46.25	43.5
	65 / 75%	8 7/8	41 5/8	32	C	F-6	60.5	46.75	43.75
	65 / 75%	8 7/8	41 5/8	33	C	G-7	62.0	47.5	44.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	Control Cable	Buss Cable
	65%	8 3/4	40	27.5	1	58.0	44.75	42.0
Cam	65%	8 3/4	40	28	1.5	58.0	44.75	42.0
&1/2	65%	8 3/4	40	28.5	2	58.0	44.75	42.0
Spiral	65%	8 3/4	40	29	2.5	58.0	44.75	42.0
	65%	8 7/8	39 5/8	29.5	3	59.5	44.75	41.75
	65%	8 7/8	39 5/8	30	3.5	59.5	44.75	41.75
	65%	8 7/8	39 5/8	30.5	4	59.5	44.75	41.75
	65%	8 7/8	40	31	4.5	61.5	45.0	41.75
	65%	8 7/8	40	31.5	5	61.5	45.0	41.75
	65%	8 7/8	40	32	5.5	61.5	45.0	41.75
	65%	8 3/4	40 3/8	32.5	6	63.5	45.25	42.25
	65%	8 3/4	40 3/8	33	6.5	63.5	45.25	42.25
	65%	8 3/4	40 3/8	33.5	7	63.5	45.25	42.25
	65%	8 7/8	40 1/4	34	7.5	64.5	45.5	41.5
	65%	8 7/8	40 1/4	34.5	8	64.5	45.5	41.5