

Model(s) MagnaTec Intruder Hunting
 Model Year 1999
 Limbs Solid Glass (16")
 Cable Guard Bar High - Short
 Limb Bolt Length 2.25

Date 2-Nov-98

Revision

Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
75%	6 7/8	39 5/8	25	2	A	54.25	41.25
75%	6 7/8	39 5/8	26	2	C	54.25	41.25
75%	6 7/8	39 5/8	27	2	E	54.25	41.25
75%	6 7/8	39 5/8	28	2	G	54.25	41.25
75%	7 1/8	39 5/8	29	3	B	57.75	41.75
75%	7 1/8	39 5/8	30	3	D	57.75	41.75
75%	7 1/8	39 5/8	31	3	G	57.75	41.75
75%	6 5/8	40 3/8	32	4	F	60.75	42.75

Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
65%	6 7/8	39 5/8	25	2	A	54.25	41.25
65%	6 7/8	39 5/8	26	2	C	54.25	41.25
65%	6 7/8	39 5/8	27	2	E	54.25	41.25
65%	6 7/8	39 5/8	28	2	G	54.25	41.25
65%	7 1/8	39 5/8	29	3	B	57.75	41.75
65%	7 1/8	39 5/8	30	3	D	57.75	41.75
65%	7 1/8	39 5/8	31	3	G	57.75	41.75
65%	6 5/8	40 3/8	32	4	F	60.75	42.75

***Letoff, brace height, axle to axle length given as a general production guide only ***

Desc: TUNE/DEFLECTION CHART - MAGNATEC INTRUDER HUNTING

File: MT - TUNE: MT INTRUDER

DATE:

2-Nov-98

HOYT USA