

Model(s) UltraTec XT 3000 Hunting and Target  
 Model Year 2002  
 Limbs XT 3000 (15 1/2")  
 Cable Guard Bar 9.50  
 Limb Bolt Length 2.5  
 Pocket 22/23

Date 8/7/2002

Revision C

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	YBC
		65%	7	40 1/8	22	1	A	52.5
	65%	7	40 1/8	23	1	D	52.5	42.0
	65%	7	40 1/8	24	1	F	52.5	42.0
Accuwheel	65%	7	40 3/8	25	2	C	54.5	42.0
AW	65%	7	40 3/8	26	2	F	54.5	42.0
2UT3H/T	65%	7	41 5/8	27	3	B	58.5	42.5
	65%	7	41 5/8	28	3	D	58.5	42.5
	65%	7	41 5/8	29	3	F	58.5	42.5
	65%	7	41 5/8	30	3	H	58.5	42.5

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	YBC
		65 / 75%	7 3/8	40 1/4	23	1	B	53.0
Command	65 / 75%	7 3/8	40 1/4	24	1	D	53.0	41.0
CL/CH	65 / 75%	7 3/8	40 1/4	25	1	F	53.0	41.0
2UT3H/T	65 / 75%	7 3/8	40 1/8	26	2	C	56.0	41.5
	65 / 75%	7 3/8	40 1/8	27	2	E	56.0	41.5
	65 / 75%	7 3/8	40 1/8	28	2	G	56.0	41.5
	65 / 75%	7 3/4	40 1/4	29	3	B	59.5	41.5
	65 / 75%	7 3/4	40 1/4	30	3	E	59.5	41.5
	65 / 75%	7 3/4	40 1/4	31	3	G	59.5	41.5
	65 / 75%	7 7/8	40 1/2	32	4	E	62.0	41.5
	65 / 75%	7 7/8	40 1/2	33	4	G	62.0	41.5

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	DT Idler	DT String	CBC	IYBC
		60 / 75%	8	39 5/8	26	1	3.0	59.0	47.0
	60 / 75%	8	39 5/8	26.5	1.5	3.0	59.0	47.0	41.5
	60 / 75%	8	39 5/8	27	2	3.0	59.0	47.0	41.5
	60 / 75%	8	39 5/8	27.5	2.5	3.0	59.0	47.0	41.5
	60 / 75%	8	39 5/8	28	3	3.0	59.0	47.0	41.5
	60 / 75%	8	39 5/8	28.5	3.5	3.0	59.0	47.0	41.5
Excel	60 / 75%	8 1/8	39 7/8	29	4	4.0	61.5	47.5	42.0
EC	60 / 75%	8 1/8	39 7/8	29.5	4.5	4.0	61.5	47.5	42.0
2UT3H/T	60 / 75%	8 1/8	39 7/8	30	5	4.0	61.5	47.5	42.0
	60 / 75%	8 1/8	39 7/8	30.5	5.5	4.0	61.5	47.5	42.0
	60 / 75%	8 1/8	39 7/8	31	6	4.0	61.5	47.5	42.0
	60 / 75%	8	40 1/2	31.5	6.5	5.0	64.0	49.0	43.0
	60 / 75%	8	40 1/2	32	7	5.0	64.0	49.0	43.0
	60 / 75%	8	40 1/2	32.5	7.5	5.0	64.0	49.0	43.0
	60 / 75%	8	40 1/2	33	8	5.0	64.0	49.0	43.0

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	DT Idler	DT String	CBC	IYBC
		60 / 75%	7 1/2	40 3/4	26	1	A-1	3	60.0	47.0
	60 / 75%	7 1/2	40 3/4	27	1	A-1	3	60.0	47.0	43.5
	60 / 75%	7 1/2	40 3/4	28	1	A-1	3	60.0	47.0	43.5
Versa	60 / 75%	7 3/4	40 3/8	29	2	C-3	4	62.0	47.5	43.5
VC	60 / 75%	7 3/4	40 3/8	30	2	C-3	4	62.0	47.5	43.5
2UT3H/T	60 / 75%	7 3/4	40 3/8	31	2	C-3	4	62.0	47.5	43.5
	60 / 75%	7 3/4	40 3/8	32	2	C-3	4	62.0	47.5	43.5
	60 / 75%	7 3/4	40 3/8	33	2	C-3	4	62.0	47.5	43.5

\*\*\*Letoff, brace height, axle to axle length given as a general production guide only\*\*\*