

Model(s) Defiant Contender Target
 Model Year 2000
 Limbs Contender
 Cable Guard Bar S/S X Long
 Limb Bolt Length 2.25
 Pocket 21

Date 12/30/1999
 Revision

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
	65%	7 1/4	44 3/8	23	1	A	56.75	46.25
	65%	7 1/4	44 3/8	24	1	C	56.75	46.25
Accuwhell	65%	7 1/4	44 3/8	25	1	F	56.75	46.25
AW	65%	7 1/4	44 1/2	26	2	B	58.75	46.25
DTOTA	65%	7 1/4	44 1/2	27	2	D	58.75	46.25
	65%	7 1/4	44 1/2	28	2	F	58.75	46.25
	65%	7 1/2	44 3/8	29	3	B	62.25	46.25
	65%	7 1/2	44 3/8	30	3	D	62.25	46.25
	65%	7 1/2	44 3/8	31	3	F	62.25	46.25
	65%	7 1/2	44 3/8	32	3	H	62.25	46.25

	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
	75 / 65%	7 1/4	44 5/8	25	1	A	57.25	46.25
Command	75 / 65%	7 1/4	44 5/8	26	1	C	57.25	46.25
CC	75 / 65%	7 1/4	44 5/8	27	1	E	57.25	46.25
DTOTC/D	75 / 65%	7 1/4	44 3/4	28	2	C	59.75	46.25
	75 / 65%	7 1/4	44 3/4	29	2	E	59.75	46.25
	75 / 65%	7 1/4	44 3/4	30	2	G	59.75	46.25
	75 / 65%	7 3/8	44 3/4	31	3	C	63.25	46.75
	75 / 65%	7 3/8	44 3/4	32	3	E	63.25	46.75
	75 / 65%	7 3/8	44 3/4	33	3	G	63.25	46.75