

Model(s) VorTec XT 3000 Hunting
 Model Year 2001
 Limbs XT 3000
 Cable Guard Bar
 Limb Bolt Length 2.5
 Pocket

Date 6/2/2016
 Revision A

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
Command C/D VT6HC/D	65%	7	38 7/8	23	1	C	51.25	46.75
	65%	7	38 7/8	24	1	D	51.25	46.75
	65%	7	38 7/8	25	1	F	51.25	46.75
	65 / 75%	6 3/4	39 3/8	26	2	C	54.25	47.25
	65 / 75%	6 3/4	39 3/8	27	2	E	54.25	47.25
	65 / 75%	6 3/4	39 3/8	28	2	G	54.25	47.25
	65 / 75%	6 3/4	39 1/4	29	3	C	57.75	47.75
	65 / 75%	6 3/4	39 1/4	30	3	E	57.75	47.75
	65 / 75%	6 3/4	39 1/4	31	3	G	57.75	47.75
	65 / 75%	6 5/8	40 1/4	32	4	E	60.25	48.25
65 / 75%	6 5/8	40 1/4	33	4	G	60.25	48.25	

Cam / Wheel	Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Idler Wheel	String	Buss Cable
	60 / 75%	7 7/8	38 1/2	26	1	3	97.25	46.25
				26.5	1.5	3	97.25	46.25
	60 / 75%	7 7/8	38 1/2	27	2	3	97.25	46.25
				27.5	2.5	3	97.25	46.25
Saber	60 / 75%	7 7/8	38 1/2	28	3	3	97.25	46.25
				28.5	3.5	3	97.25	46.25
B	60 / 75%	8	38 3/4	29	4	4	99.75	46.75
				29.5	4.5	4	99.75	46.75
VT6HB	60 / 75%	8	38 3/4	30	5	4	99.75	46.75
				30.5	5.5	4	99.75	46.75
	60 / 75%	8	38 3/4	31	6	4	99.75	46.75
				31.5	6.5	4	99.75	46.75
	60 / 75%	8 3/8	38 3/8+	32	7	5	101.75	46.75
				32.5	7.5	5	101.75	46.75
				33	8	5	101.75	46.75