

Model(s) Raider Intruder Hunting  
 Model Year 1999  
 Limbs Solid Glass (16")  
 Cable Guard Bar Single Bend  
 Limb Bolt Length 2.5

Date 2-Nov-98

Revision

Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
75%	7 5/8	39 3/4	25	2	A	54.75	41.25
75%	7 5/8	39 3/4	26	2	C	54.75	41.25
75%	7 5/8	39 3/4	27	2	E	54.75	41.25
75%	7 5/8	39 3/4	28	2	G	54.75	41.25
75%	7 5/8	39 3/4	29	3	B	58.25	41.75
75%	7 5/8	39 3/4	30	3	D	58.25	41.75
75%	7 5/8	39 3/4	31	3	F	58.25	41.75
75%	7 5/8	39 3/4	32	3	H	58.25	41.75

Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	Module Position	String	Buss Cable
65%	7 5/8	39 3/4	25	2	A	54.75	41.25
65%	7 5/8	39 3/4	26	2	C	54.75	41.25
65%	7 5/8	39 3/4	27	2	E	54.75	41.25
65%	7 5/8	39 3/4	28	2	G	54.75	41.25
65%	7 5/8	39 3/4	29	3	B	58.25	41.75
65%	7 5/8	39 3/4	30	3	D	58.25	41.75
65%	7 5/8	39 3/4	31	3	F	58.25	41.75
65%	7 5/8	39 3/4	32	3	H	58.25	41.75

\*\*\*Letoff, brace height, axle to axle length given as a general production guide only\*\*\*

Desc: TUNE/DEFLECTION CHART - RAIDER INTURDER HUNTING  
 File: RD - TUNE: RD INTRUDER DATE: 2-Nov-98  
 HOYT USA