

Model(s) UltraElite
Model Year 2007
Limbs XT3000
Cable Guard Bar 9 1/2
Limb Bolt Length 2 1/2
Pocket 31 & 32

Date

Revision

	% Lutoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
cam & 1/2	65/75	7 7/16	41	27	E	C&1/2 #1	54.25	44.5	42.25
	65/75	7 1/2	41 1/16	28	E	C&1/2 #2	55.25	44.75	42.5
	65/75	7 7/16	41 1/4	29	E	C&1/2 #3	56.5	45.5	42.75
	65/75	7 3/8	41 1/4	30	E	C&1/2 #4	58	46	43.25
	65/75	7 3/8	41 3/8	31	E	C&1/2 #5	59.25	46.25	43.5
	65/75	7 7/16	41 1/2	32	E	C&1/2 #6	60.5	46.75	43.75
	65/75	7 9/16	41 1/2	33	E	C&1/2 #7	61.75	47.25	43.75

	% Lutoff	Brace Height	Axle to Axle	Draw Length		Base Cam	String	control Cable	Buss Cable	Cam Size
C2 - cam	65%	7 5/16	40 3/16	26		1/2	54.25	45.25	42.25	Base Size 1
	65%	7 5/16	40 3/16	26 1/2		1	54.25	45.25	42.25	
	65%	7 5/16	40 3/16	27		1 1/2	54.25	45.25	42.25	
	65%	7 5/16	40 3/16	27 1/2		2	54.25	45.25	42.25	Base Size 2
	65%	7 3/8	40 1/4	28		2 1/2	56.75	45.25	42.75	
	65%	7 3/8	40 1/4	28 1/2		3	56.75	45.25	42.75	
	65%	7 3/8	40 1/4	29		3 1/2	56.75	45.25	42.75	Base Size 3
	65%	7 5/16	40 11/16	29 1/2		4	59.25	45.75	43.25	
	65%	7 5/16	40 5/8	30		4 1/2	59.25	45.75	43.25	
	65%	7 5/16	40 5/8	30 1/2		5	59.25	45.75	43.25	Base Size 4
	65%	7 3/8	41	31		5 1/2	62.25	46.25	43.5	
	65%	7 3/8	41	31 1/2		6	62.25	46.25	43.5	
	65%	7 3/8	41	32		6 1/2	62.25	46.25	43.5	Base Size 5
	65%	7 7/16	41 1/8	32 1/2		7	65	46.5	43.75	
	65%	7 7/16	41 1/8	33		7 1/2	65	46.5	43.75	
65%	7 7/16	41 1/8	33 1/2		8	65	46.5	43.75		