

Contender - XT2000 - Spiral X Cam & 1/2

CAM	LETOFF	BRACE HEIGHT	AXLE TO AXLE	DRAW LENGTH	MODULE POSITION	BASE CAM	STRING	CONTROL CABLE	BUSS CABLE	CAM FAMILY
Spiral X Cam	65%	6 5/8	38 1/2	24	N/A	0.5	56.25	42.88	40.25	Size 1
	65%	6 5/8	38 1/2	24 1/2	N/A	1	56.25	42.88	40.25	
	65%	6 5/8	38 1/2	25	N/A	1.5	56.25	42.88	40.25	
	65%	6 5/8	38 1/2	25 1/2	N/A	2	56.25	42.88	40.25	
	65%	6 5/8	38 1/2	26	N/A	2.5	56.25	42.88	40.25	
	65%	6 7/8	38	26 1/2	N/A	3	57.50	43.25	40.25	Size 2
	65%	6 7/8	38	27	N/A	3.5	57.50	43.25	40.25	
	65%	6 7/8	38	27 1/2	N/A	4	57.50	43.25	40.25	
	65%	6 7/8	38 1/4	28	N/A	4.5	59.50	43.25	40.00	Size 3
	65%	6 7/8	38 1/4	28 1/2	N/A	5	59.50	43.25	40.00	
	65%	6 7/8	38 1/4	29	N/A	5.5	59.50	43.25	40.00	
	65%	6 5/8	38 3/4	29 1/2	N/A	6	61.50	43.50	40.50	Size 4
	65%	6 5/8	38 3/4	30	N/A	6.5	61.50	43.50	40.50	
	65%	6 5/8	38 3/4	30 1/2	N/A	7	61.50	43.50	40.50	
	65%	6 3/4	38 5/8	31	N/A	7.5	62.75	44.25	40.13	Size 5
	65%	6 3/4	38 5/8	31 1/2	N/A	8	62.75	44.25	40.13	

* = Shipped module position

Contender - XT2000 - GTX Cam & 1/2

CAM	LETOFF	BRACE HEIGHT	AXLE TO AXLE	DRAW LENGTH	MODULE POSITION	BASE CAM	STRING	CONTROL CABLE	BUSS CABLE	CAM FAMILY
	65/75 %	7 1/8	37 1/2	24	B	#1	50.25	41.25	39.00	N/A
	65/75 %	7 1/8	37 1/2	24 1/2	C	#1	50.25	41.25	39.00	N/A
	65/75 %	7 1/8	37 1/2	25	D*	#1	50.25	41.25	39.00	N/A
	65/75 %	7 1/8	37 1/2	25 1/2	E	#1	50.25	41.25	39.00	N/A
	65/75 %	7 1/8	37 3/4	25	B	#2	51.50	41.75	39.50	N/A
	65/75 %	7 1/8	37 3/4	25 1/2	C	#2	51.50	41.75	39.50	N/A
	65/75 %	7 1/8	37 3/4	26	D*	#2	51.50	41.75	39.50	N/A
	65/75 %	7 1/8	37 3/4	26 1/2	E	#2	51.50	41.75	39.50	N/A
	65/75 %	7 1/8	38 1/4	26	B	#3	53.25	42.25	40.00	N/A
	65/75 %	7 1/8	38 1/4	26 1/2	C	#3	53.25	42.25	40.00	N/A
	65/75 %	7 1/8	38 1/4	27	D*	#3	53.25	42.25	40.00	N/A
	65/75 %	7 1/8	38 1/4	27 1/2	E	#3	53.25	42.25	40.00	N/A
	65/75 %	7 1/8	38 5/8	27	B	#4	54.50	42.25	40.00	N/A
	65/75 %	7 1/8	38 5/8	27 1/2	C	#4	54.50	42.25	40.00	N/A
	65/75 %	7 1/8	38 5/8	28	D*	#4	54.50	42.25	40.00	N/A
	65/75 %	7 1/8	38 5/8	28 1/2	E	#4	54.50	42.25	40.00	N/A
	65/75 %	7 1/4	38 3/4	28	B	#5	56.50	42.75	40.50	N/A
	65/75 %	7 1/4	38 3/4	28 1/2	C	#5	56.50	42.75	40.50	N/A
	65/75 %	7 1/4	38 3/4	29	D*	#5	56.50	42.75	40.50	N/A
	65/75 %	7 1/4	38 3/4	29 1/2	E	#5	56.50	42.75	40.50	N/A
	65/75 %	7 1/4	38 1/2	29	B	#6	57.50	42.75	40.75	N/A
	65/75 %	7 1/4	38 1/2	29 1/2	C	#6	57.50	42.75	40.75	N/A
	65/75 %	7 1/4	38 1/2	30	D*	#6	57.50	42.75	40.75	N/A
	65/75 %	7 1/4	38 1/2	30 1/2	E	#6	57.50	42.75	40.75	N/A

Date: 10/15/12

Model: Contender

Limb: XT2000

Stealth Shot Bar: N/A

Pocket: #35 & #38

Model Year: 2013

Cable Guard: 9.00

Limb Bolt Length: 2.5

Rocker: #6 String Model: FS

PE-9999-991 Contender XT 2000 tune chart

Zak Kurtzhals, 11/1/2012