

Model(s) UltraTec
 Model Year 2005
 Limbs XT3000
 Cable Guard Bar 9 1/2
 Limb Bolt Length 2 1/2
 Pocket Triton #25&26

Date 1/26/2005

Revision A

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
cam & 1/2 adjustable	65/75	7 1/8	40 5/8	26	D	A	53.5	44.5	42.25
	65/75	7 1/4	40 1/2	27	D	B	54.5	44.75	42.25
	65/75	7 1/4	40 1/2	28	D	C	55.5	44.75	42.25
	65/75	7 1/4	40 1/4	29	D	D	56.5	45	42.25
	65/75	7 5/8	40 1/2	30	D	E	58	45.25	42.5
	65/75	7 3/4	40 5/8	31	D	F	59.5	45.75	42.75
	65/75	7 5/8	41	32	D	G	61	46.5	43

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
cam & 1/2 spiral	65%	7 1/8	40	26	1.0	58	44.5	41.75
	65%	7 1/8	40	26 1/2	1.5	58	44.5	41.75
	65%	7 1/8	40	27	2.0	58	44.5	41.75
	65%	7 1/8	40	27 1/2	2.5	58	44.5	41.75
	65%	7 3/8	39 1/2	28	3.0	59.5	44.5	41.5
	65%	7 3/8	39 1/2	28 1/2	3.5	59.5	44.5	41.5
	65%	7 3/8	39 1/2	29	4.0	59.5	44.5	41.5
	65%	7 3/8	39 3/4	29 1/2	4.5	61.5	44.75	41.5
	65%	7 3/8	39 3/4	30	5.0	61.5	44.75	41.5
	65%	7 3/8	39 3/4	30 1/2	5.5	61.5	44.75	41.5
	65%	7 3/8	40	31	6.0	63	44.5	41.5
	65%	7 3/8	40	31 1/2	6.5	63	44.5	41.5
	65%	7 3/8	40	32	7.0	63	44.5	41.5
	65%	7 3/8	40	32 1/2	7.5	64.5	45.25	41.25
	65%	7 3/8	40	33	8.0	64.5	45.25	41.25

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
wheel & 1/2	65%	7 5/8	39 1/2	24 1/2	0.0	56.5	43.75	40.75
	65%	7 5/8	39 1/2	25	0.5	56.5	43.75	40.75
	65%	7 5/8	39 1/2	25 1/2	1.0	56.5	43.75	40.75
	65%	7 5/8	39 1/2	26	1.5	56.5	43.75	40.75
	65%	7 5/8	39 1/2	26 1/2	2.0	56.5	43.75	40.75
	65%	7 5/8	39 1/2	27	2.5	56.5	44	40.75
	65%	7 5/8	39 1/2	27 1/2	3.0	56.5	44	40.75
	65%	7 3/4	39 1/2	28	3.5	60	45	41
	65%	7 3/4	39 1/2	28 1/2	4.0	60	45	41
	65%	7 3/4	39 1/2	29	4.5	60	45	41
	65%	7 3/4	39 1/2	29 1/2	5.0	60	45	41
	65%	7 3/4	39 1/2	30	5.5	60	45	41
	65%	7 7/8	40	30 1/2	6.0	64.5	46.5	41.75
	65%	7 7/8	40	31	6.5	64.5	46.5	41.75
	65%	7 7/8	40	31 1/2	7.0	64.5	46.5	41.75
	65%	7 7/8	40	32	7.5	64.5	46.5	41.75
	65%	7 7/8	40	32 1/2	8.0	64.5	46.5	41.75