

Model(s) ProElite
Model Year 2007
Limbs XT3000
Cable Guard Bar 10 1/2
Limb Bolt Length 2 1/2
Pocket 31 & 32

Date

Revision

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
adjustable	65/75	8 1/2	41	28	E	C&1/2 #1	54.25	44.5	42.25
	65/75	8 1/2	41 1/8	29	E	C&1/2 #2	55.25	44.75	42.5
	65/75	8 5/8	41 1/4	30	E	C&1/2 #3	56.5	45.5	42.75
	65/75	8 5/8	41 1/4	31	E	C&1/2 #4	58	46	43.25
	65/75	8 5/8	41 3/8	32	E	C&1/2 #5	59.25	46.25	43.5
	65/75	8 3/4	41 5/8	33	E	C&1/2 #6	60.5	46.75	43.75
	65/75	8 7/8	41 1/2	34	E	C&1/2 #7	61.75	47.25	43.75

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length		Base Cam	String	control Cable	Buss Cable	Cam Size
C2	65%	8 9/16	39 13/16	27		0.5	54.25	45.25	42.25	Base Size 1
	65%	8 9/16	39 7/8	27 1/2		1	54.25	45.25	42.25	
	65%	8 9/16	39 7/8	28		1.5	54.25	45.25	42.25	
	65%	8 9/16	39 7/8	28 1/2		2	54.25	45.25	42.25	
	65%	8 9/16	40 3/16	29		2.5	56.75	45.25	42.75	Base Size 2
	65%	8 9/16	40 1/4	29 1/2		3	56.75	45.25	42.75	
	65%	8 9/16	40 5/16	30		3.5	56.75	45.25	42.75	
	65%	8 1/2	40 5/8	30 1/2		4	59.25	45.75	43.25	Base Size 3
	65%	8 1/2	40 11/16	31		4.5	59.25	45.75	43.25	
	65%	8 9/16	40 11/16	31 1/2		5	59.25	45.75	43.25	Base Size 4
	65%	8 9/16	41	32		5.5	62.25	46.25	43.5	
	65%	8 9/16	41 1/16	32 1/2		6	62.25	46.25	43.5	
65%	8 9/16	41 1/16	33		6.5	62.25	46.25	43.5		