

Model(s) **ProElite**  
 Model Year **2005**  
 Limbs **XT2000**  
 Cable Guard Bar **9 1/2**  
 Limb Bolt Length **2 1/2**  
 Pocket **Triton #27&28**

Date **11/23/2004**

Revision

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
	65/75	7 7/8	38 1/8	26	D	A	51	42	39.75
cam	65/75	7 7/8	38 1/4	27	D	B	52	42.25	40
& 1/2	65/75	8 1/8	38	28	C	C	53	42.25	39.75
adjustable	65/75	8 1/8	38 1/8	29	C	D	54.5	43	40.25
	65/75	8 3/8	38	30	C	E	55.5	42.75	40
	65/75	8 3/8	38 1/8	31	C	F	57	43.25	40.25
	65/75	8 1/2	38 1/4	32	C	G	58.5	44	40.5

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
	65%	8	37	26	1.0	55	41.5	39
	65%	8	37	26 1/2	1.5	55	41.5	39
	65%	8	37	27	2.0	55	41.5	39
	65%	8	37	27 1/2	2.5	55	41.5	39
	65%	8 1/8	36 5/8	28	3.0	56.5	41.75	38.75
	65%	8 1/8	36 5/8	28 1/2	3.5	56.5	41.75	38.75
cam	65%	8 1/8	36 5/8	29	4.0	56.5	41.75	38.75
& 1/2	65%	8 1/4	36 7/8	29 1/2	4.5	58.5	42	38.75
spiral	65%	8 1/4	36 7/8	30	5.0	58.5	42	38.75
	65%	8 1/4	36 7/8	30 1/2	5.5	58.5	42	38.75
	65%	8	37 1/2	31	6.0	60.5	42.25	39.25
	65%	8	37 1/2	31 1/2	6.5	60.5	42.25	39.25
	65%	8	37 1/2	32	7.0	60.5	42.25	39.25
	65%	8 1/4	37	32 1/2	7.5	61.5	42.5	38.5
	65%	8 1/4	37	33	8.0	61.5	42.5	38.5