

Model(s) **UltraElite**  
 Model Year **2005**  
 Limbs **XT3000**  
 Cable Guard Bar **9 1/2**  
 Limb Bolt Length **2 1/2**  
 Pocket **Triton #27&28**

Date **1/26/2005**

Revision **B**

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
cam & 1/2 adjustable	65/75	7	41 3/4	26	D	A	54.5	45.5	43.25
	65/75	7 1/8	41 3/4	27	D	B	55.5	45.75	43.5
	65/75	7 1/4	41 1/2	28	C	C	56.5	45.75	43.25
	65/75	7 3/8	41 5/8	29	C	D	58	46.25	43.5
	65/75	7 1/2	41 1/2	30	C	E	59	46.25	43.5
	65/75	7 1/2	41 5/8	31	C	F	60.5	46.75	43.75
	65/75	7 1/2	41 5/8	32	C	G	62	47.5	44

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
cam & 1/2 spiral	65%	7 1/2	40	26	1.0	58	44.75	42
	65%	7 1/2	40	26 1/2	1.5	58	44.75	42
	65%	7 1/2	40	27	2.0	58	44.75	42
	65%	7 1/2	40	27 1/2	2.5	58	44.75	42
	65%	7 5/8	39 5/8	28	3.0	59.5	44.75	41.75
	65%	7 5/8	39 5/8	28 1/2	3.5	59.5	44.75	41.75
	65%	7 5/8	39 5/8	29	4.0	59.5	44.75	41.75
	65%	7 5/8	40	29 1/2	4.5	61.5	45	41.75
	65%	7 5/8	40	30	5.0	61.5	45	41.75
	65%	7 5/8	40	30 1/2	5.5	61.5	45	41.75
	65%	7 1/2	40 3/8	31	6.0	63.5	45.25	42.25
	65%	7 1/2	40 3/8	31 1/2	6.5	63.5	45.25	42.25
	65%	7 1/2	40 3/8	32	7.0	63.5	45.25	42.25
	65%	7 3/4	40 1/4	32 1/2	7.5	64.5	45.5	41.5
	65%	7 3/4	40 1/4	33	8.0	64.5	45.5	41.5

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
wheel & 1/2	65%	7 1/2	40 1/2	25	0.0	57.5	44.75	41.75
	65%	7 1/2	40 1/2	25 1/2	0.5	57.5	44.75	41.75
	65%	7 1/2	40 1/2	26	1.0	57.5	44.75	41.75
	65%	7 1/2	40 1/2	26 1/2	1.5	57.5	44.75	41.75
	65%	7 1/2	40 1/2	27	2.0	57.5	44.75	41.75
	65%	7 1/2	40 1/2	27 1/2	2.5	57.5	45	41.75
	65%	7 1/2	40 1/2	28	3.0	57.5	45	41.75
	65%	7 3/4	40 1/2	28 1/2	3.5	61	46	42
	65%	7 3/4	40 1/2	29	4.0	61	46	42
	65%	7 3/4	40 1/2	29 1/2	4.5	61	46	42
	65%	7 3/4	40 1/2	30	5.0	61	46	42
	65%	7 3/4	40 1/2	30 1/2	5.5	61	46	42
	65%	7 3/4	41	31	6.5	65.5	47.5	42.75
	65%	7 3/4	41	31 1/2	7.0	65.5	47.5	42.75
	65%	7 3/4	41	32	7.5	65.5	47.5	42.75
	65%	7 3/4	41	32 1/2	8.0	65.5	47.5	42.75