

Model(s) **UltraElite**
 Model Year **2006**
 Limbs **XT2000**
 Cable Guard Bar **8 1/2**
 Limb Bolt Length **2 1/2**
 Pocket **31 & 32**

Date **12/8/2005**

Revision

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
	65/75	6 3/4	37 7/8	25	D	C&1/2 #1	51	41.5	39.25
cam	65/75	6 15/16	37 3/4	26	D	C&1/2 #2	52	41.5	39.25
& 1/2	65/75	7	37 11/16	27	D	C&1/2 #3	52.75	42	39.25
adjustable	65/75	7 1/16	37 3/8	28	D	C&1/2 #4	54	42.5	39.75
	65/75	7 1/16	37 5/8	29	D	C&1/2 #5	55.5	42.5	39.75
	65/75	7 3/16	37 13/16	30	D	C&1/2 #6	57	43	40
	65/75	7 5/16	37 7/8	31	D	C&1/2 #7	58.25	43.5	40

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
	65%	6 9/16	37 1/4	24 1/2	1.0	55.25	41.75	39.25
	65%	6 9/16	37 1/4	25	1.5	55.25	41.75	39.25
	65%	6 9/16	37 1/4	25 1/2	2.0	55.25	41.75	39.25
	65%	6 9/16	37 1/4	26	2.5	55.25	41.75	39.25
	65%	6 5/8	37 1/4	26 1/2	3.0	57	42.25	39.25
	65%	6 5/8	37 1/4	27	3.5	57	42.25	39.25
cam	65%	6 5/8	37 1/4	27 1/2	4.0	57	42.25	39.25
& 1/2	65%	6 5/8	37 3/8	28	4.5	59	42.25	39
spiral	65%	6 5/8	37 3/8	28 1/2	5.0	59	42.25	39
	65%	6 5/8	37 3/8	29	5.5	59	42.25	39
	65%	6 5/8	37 5/8	29 1/2	6.0	60.5	42.25	39.25
	65%	6 5/8	37 5/8	30	6.5	60.5	42.25	39.25
	65%	6 5/8	37 5/8	30 1/2	7.0	60.5	42.25	39.25
	65%	6 5/8	37 5/8	31	7.5	62.25	43.25	39.25
	65%	6 5/8	37 5/8	31 1/2	8.0	62.25	43.25	39.25