

Model(s) ProElite  
 Model Year 2006  
 Limbs XT3000  
 Cable Guard Bar 10 1/2  
 Limb Bolt Length 2 1/2  
 Pocket 31 & 32

Date 12/8/2005

Revision

Cam / Wheel	% Lutoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
cam & 1/2 adjustable	65/75	8 1/2	41	28	E	C&1/2 #1	54.25	44.5	42.25
	65/75	8 1/2	41 1/8	29	E	C&1/2 #2	55.25	44.75	42.5
	65/75	8 5/8	41 1/4	30	E	C&1/2 #3	56.5	45.5	42.75
	65/75	8 5/8	41 1/4	31	E	C&1/2 #4	58	46	43.25
	65/75	8 5/8	41 3/8	32	E	C&1/2 #5	59.25	46.25	43.5
	65/75	8 3/4	41 5/8	33	E	C&1/2 #6	60.5	46.75	43.75
	65/75	8 7/8	41 1/2	34	E	C&1/2 #7	61.75	47.25	43.75

Cam / Wheel	% Lutoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
cam & 1/2 spiral	65%	8 3/8	40 1/8	27	1.0	58.25	44.75	42
	65%	8 3/8	40 1/8	27 1/2	1.5	58.25	44.75	42
	65%	8 3/8	40 1/8	28	2.0	58.25	44.75	42
	65%	8 3/8	40 1/8	28 1/2	2.5	58.25	44.75	42
	65%	8 1/2	39 7/8	29	3.0	59.75	45	42
	65%	8 1/2	39 7/8	29 1/2	3.5	59.75	45	42
	65%	8 1/2	39 7/8	30	4.0	59.75	45	42
	65%	8 1/2	40 1/4	30 1/2	4.5	61.75	45	41.75
	65%	8 1/2	40 1/4	31	5.0	61.75	45	41.75
	65%	8 1/2	40 1/4	31 1/2	5.5	61.75	45	41.75
	65%	8 1/2	40 1/4	32	6.0	63.25	45	42
	65%	8 1/2	40 1/4	32 1/2	6.5	63.25	45	42
	65%	8 1/2	40 1/4	33	7.0	63.25	45	42
	65%	8 1/2	40 3/8	33 1/2	7.5	64.5	46	42
65%	8 1/2	40 3/8	34	8.0	64.5	46	42	

Cam / Wheel	% Lutoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
wheel & 1/2	65%	8 3/4	40 5/8	26	0.0	57	44.75	41.75
	65%	8 3/4	40 5/8	26 1/2	0.5	57	44.75	41.75
	65%	8 3/4	40 5/8	27	1.0	57	44.75	41.75
	65%	8 3/4	40 5/8	27 1/2	1.5	57	44.75	41.75
	65%	8 3/4	40 5/8	28	2.0	57	44.75	41.75
	65%	8 3/4	40 5/8	28 1/2	2.5	57	45	41.75
	65%	8 3/4	40 5/8	29	3.0	57	45	41.75
	65%	8 7/8	40 5/8	29 1/2	3.5	60.75	46	42
	65%	8 7/8	40 5/8	30	4.0	60.75	46	42
	65%	8 7/8	40 5/8	30 1/2	4.5	60.75	46	42
	65%	8 7/8	40 5/8	31	5.0	60.75	46	42
	65%	8 7/8	40 5/8	31 1/2	5.5	60.75	46	42
	65%	8 7/8	40 5/8	32	6.0	60.75	46	42
	65%	8 7/8	40 7/8	32 1/2	6.5	65	47.5	42.75
	65%	8 7/8	40 7/8	33	7.0	65	47.5	42.75
	65%	8 7/8	40 7/8	33 1/2	7.5	65	47.5	42.75
	65%	8 7/8	40 7/8	34	8.0	65	47.5	42.75